

VRF INDOOR FRESH AIR DUCTED UNIT

Model			STA-125VIHDDFA	STA-140VIHDDFA	STA-200VIHDDFA
Power supply		V- Ph-Hz	1-phase,220-240V, 50/60Hz		
Cooling	Capacity	kW	12.5	14	20
	Power Input	W	480	480	850
Air flow rate		m ³ /h	2000/1917/1833/1750/1667/1583/1500		3000/2833/2667/2500/2333/2167/2000
External static pressure		Pa	150(100~250)		200(100~400)
Sound pressure level			48/47/46/45/44/43/42		50/49/48/47/46/44/43
Indoor unit	Net dimensions (W×H×D)	mm	1322x423x691		1454x515x931
	Packed dimensions (W×H×D)	mm	1436450x768		1509x550x990
	Net/Gross weight	kg	68/76		130/142
Pipe connections	Liquid / Gas	mm	Φ9.53//Φ15.9		Φ12.7/Φ22.2
	Drain pipe	mm	OD Φ25		OD Φ32

VRF INDOOR FRESH AIR DUCTED UNIT

Model			STA-250VIHDDFA	STA-280VIHDDFA	STA-450VIHDDFA	STA-560VIHDDFA
Power supply		V- Ph-Hz	1-phase,220-240V, 50/60Hz			
Cooling	Capacity	kW	25	28	45	56
	Power Input	W	850	850	1080	2272
Air flow rate		m ³ /h	3000/2833/2667/2500/2333/2167/2000		4200/3967/3733/3500/3267/3033/2800	6000/5665/5330/5000/4665/4330/4000
External static pressure		Pa	200(100~400)	300(100~400)	300(100~400)	300(100~400)
Sound pressure level			50/49/48/47/46/44/43		58/56/55/53/51/49/48	59/57/56/55/53/51/50
Indoor unit	Net dimensions (W×H×D)	mm	1454x515x931		2010x680x905	2010x680x905
	Packed dimensions (W×H×D)	mm	1509x550x990		2095x800x964	2095x800x964
	Net/Gross weight	kg	130/142		195/215	218/248
Pipe connections	Liquid / Gas	mm	Φ12.7/Φ22.2		Φ15.9/Φ28.6	Φ15.9/Φ28.6
	Drain pipe	mm	OD Φ32			